



Product Data Sheet

Regional Paints 1K Acrylic Sprays

Description

Solo Active spray is a fast drying tough durable acrylic top coat with good protection against weathering, ideal for a quick repair on cars, commercial vehicles and many other industries.

It is recommended to use our Solo Active Primer as an undercoat or our Solo Active+ High Build & Etch Primer if painting over bare metal or a recoatable plastic.

Directions for use

SHAKE CAN FOR AT LEAST TWO MINUTES BEFORE USE

Prepare the area to be painted, ensuring it to be free from dirt, wax, oil, etc.

Mask off with masking paper and masking tape to prevent any overspray.

Use between 15 to 25°C in a well ventilated area.

Shake can vigorously for at least two minutes to ensure the paint is thoroughly mixed.

Repeat shaking at regular intervals during use.

Spray from a distance of 20cm to 25cm.

Apply several light coats with up to 10 minute intervals between coats to achieve the best result.

The number of coats required depends on the colour being painted.

After use invert can and spray to clear the valve and sprayhead, this prevents the aerosol from clogging up prior to using next time. If sprayhead should clog, remove and clean with solvent.

Product Part No.

Satin Black	SOLO-SB
Matt Black	SOLO-MB
Gloss Black	SOLO-GB
Gloss White	SOLO-GW

UFI Ref

Satin Black	6SH1-4XAX-VTOF-DTNH
Matt Black	1XH1-4XQR-GTOF-QGTN
Gloss Black	J4J 1-5X3J-3TOF -1 SYS
Gloss White	ST J1-6XMQ-JTOD-AWN9

VOC Content

Satin Black	633
Matt Black	643
Gloss Black	636
Gloss White	619