



Product Data Sheet

Regional Paints High Build & Etch

Description

Solo Active + High Build & Etch Primer, is a fast drying, self etching high build & etch primer with high filling power and protection against corrosion.

Adheres to Iron, Zinc, Steel, Aluminium and most recoatable plastics.

Ideal for a quick repair on cars, commercial vehicles and many other industries.

Can be overcoated with 1 K, 2K or Waterbased paints.

Directions for use

SHAKE CAN FOR AT LEAST TWO MINUTES BEFORE USE

Prepare the area to be painted, ensuring it to be free from dirt, wax, oil, etc.

Lightly abrade the surface, mask off with masking paper and masking tape to prevent any overspray.

Use between 15 to 25°C in a well ventilated area.

Shake can vigorously for at least two minutes to ensure the primer is thoroughly mixed.

Repeat shaking at regular intervals during use.

Spray from a distance of 20cm to 25cm.

Apply several light coats with up to 10 minutes intervals between coats to achieve the best results.

The number of coats depends on the colour that is being over painted.

Sandable after approx 30 minutes at 20°C.

After use invert can and spray to clear the valve and sprayhead, this prevents the aerosol from clogging up prior to using next time.

Product Part No.

Light Grey	SOLO-HBE-LG
Dark Grey	SOLO-HBE-DG
Black	SOLO-HBE-BL
White	SOLO-HBE-WH

UFI Ref

Light Grey	7NG1 -JXCS-WT01-SD2P
Dark Grey	0UG1 .JXRK-HT01-327T
Black	NNK1-8XHP-MTOC-XAFX
White	XUK1-8XWG-7TOC-80N2

VOC Content

Light Grey	627
Dark Grey	623
Black	628
White	629

This information is provided in good faith based upon data and sources believed to be reliable and correct.

Conditions of use, outside the control of the company, dictate that no responsibility can be assumed for the ultimate performance of this product.